DT2063N

Wärmemelder, 2LEDs, 2000er Serie



DT2063N

Wärmemelder, 2LEDs, 2000er Serie

Technische Spezifikationen

General

Addressing method	Rotary switch

Electrical

Power supply type	Alimentato ad anello

Detection

Monitoring	Alarm threshold
Alarm temperature (typical)	> +40°C

Physical

Colour	Bianco nuvola (RAL 9001)
Mounting type	Deckenmontage
Material (body)	Plastik

Environmental

Vandal proof	No
Application temperature (typical)	+25°C
Environment	Drinnen

Regulatory

Compliancy	CE, REACH, RoHS 3, WEEE
Certification	CPR

Kompatible Produkte

Kategorie	Referenz	Beschreibung
Detection device	DB2002	Niedriger Sockel, Aufputz, 2000er Serie
Detection device	DB2004	Hoher Sockel mit Ausgang für Parallelanzeige, 2000er Serie
Detection device	DB2016	Isolatorsockel mit Ausgang für Parallelanzeige, 2000er Serie, G203028
Notification device	AI672	Parallelanzeige mit 2 LEDs
Notification device	AI673	Parallelanzeige optisch/akustisch 4 mA
Notification device	DB2368IAS-W	Signalgeber mit Isolatorsockel für Ringl Weiss, 2000er Serie, Multitone

KIDDE GLOBAL SOLUTIONS

Als innovatives Unternehmen behält sich Kidde Global Solutions das Recht vor, Produktspezifikationen ohne Ankündigungen zu ändern. Für die aktuellsten Produktspezifikationen, besuchen Sie bitte de.firesecurityproducts.com online oder kontaktieren Sie bitte unsere Vertriebsmitarbeiter.