BS123N

Battery, 12 V, 3.2 Ah



Details

- Maintenance free
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechangeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

BS123N
Battery, 12 V, 3.2 Ah

Technical specifications

General

Product type	Forseglet blybatteri

Electrical Characteristics

Nominal voltage	12 V
Nominal capacity	3 Ah
Internal approx. resistance	43 mOhm

Charge / discharge

Max. charge voltage	15 VDC at +25°C
Max. charge current	0.96 A
Max. discharge current	48 A

Temperature

Charging temperature	0 to +40°C
Discharging temperature	-15 to +50°C

Physical

Physical dimensions	133 x 97 x 33 mm
Net weight	1.12 kg
Shipping weight	1.12 kg
Material	ABS
Terminal type	Fast-on tab 187

Environmental

Fire retardant	No
Operating temperature	-15 to +40°C
Storage temperature	-15 to +50°C

Regulatory

Compliancy	CE, RoHS 2, WEEE

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 21 January 2026 - 19:53