PS48VDC100W-DIN

48 VDC, 100 W, power supply with DIN rail mount

Overview

KGS Fire & Security's wide range of power supplies provide solutions for all the majority of various applications. Available in wall format with adaptors, KGS Fire & Security supplies can be used with all major power plugs. Solutions include both in wall and “power brick” configurations. Switching supplies include advanced technology and power savings, meeting Level V (5) International Efficiency in compliance with California Energy Commission, Energy Star and the EU Code of Conduct for external power supplies. Supplies can be mixed and matched to a variety of KGS Fire & Security products to meet installation requirements.



Details

- CE approved
- UL approved
- CSA approved
- Compact power supplies for use with PoE Switches Media Converters
- Low voltage outputs
- Models for Europe and UK region
- In line power supply

PS48VDC100W-DIN

48 VDC, 100 W, power supply with DIN rail mount

Technical specifications

Electrical

Mains input	90 to 264 VAC, 47 to 63 Hz

Output

Power output voltage	48 VDC
Power output current mains	2 A

Physical

Physical dimensions	55 x 90 x 100 mm
Net weight	420 g
Colour	Hvid
Form factor	DIN skinne monteret

Regulatory

Compliancy	CE, REACH, RoHS 2, WEEE

Standards Conformance

EMC	CISPR 22 Class B
EMC	EN55022 Class B
EMC	EN61204-3 Class B
EMC	FCC parts 15 Class B
BSMI : EMS requirements	EN55024
BSMI : EMS requirements	IEC-61000-4-2
BSMI : EMS requirements	IEC-61000-4-3
BSMI : EMS requirements	IEC-61000-4-4
BSMI : EMS requirements	IEC-61000-4-5
BSMI : EMS requirements	IEC-61000-4-6
BSMI : EMS requirements	IEC-61000-4-8
BSMI : EMS requirements	IEC-61000-4-11

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 21 January 2026 - 19:55