PSU-3.5A

Universal 12 VDC, 3.5 A power supply

Overview

The PSU3.5A is a 3.5A 12V encapsulated power supply which is suitable for use with all TruVision and UltraView cameras.

The unit features a universal mains input voltage range from 100 to 240V ac and includes electronic short circuit protection and mains status indication. It also has high efficiency switch mode operation which means lower running temperatures and lower running costs.

The unit is specifically designed for CCTV applications, meaning it provides high reliability and performance with low maintenance and operational costs.



PSU-3.5A

Universal 12 VDC, 3.5 A power supply

Technical specifications

General

Length of mains lead	Approx. 1200 mm
Length of output power lead	Approx. 1500 mm
Compatible products	TruVision Monitors

Output

Power output voltage	12 VDC
Power output current	3.5 A

Electrical

Mains input	100 to 240 VAC @ 50 Hz
Power plug type	EU, UK

Physical

Physical dimensions	112 x 54 x 32mm
Net weight	280 g
Colour	Sort
Form factor	Ekstern adapter

Environmental

Operating temperature	-10 to 40°C
Relative humidity	95 %
Environment	Indendør

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 18 June 2026 - 14:26