# VE1012PI

**Vector PIR, 9 curtains, 12 m, Pet Immune**



## Details

- Passive Infra Red motion sensor
- 3-Brid Gliding Focus Curtain mirror
- Plug-in electronics
- Sealed optics
- "V2E" signal processing for false alarm immunity
- 15Kg pet tolerance
- Under crawl detection
- Selectable coverage pattern using mirror masks
- Auto focus with constant range sensitivity
- No adjustment required for different mounting heights
- Tolerates wall angle deviation
- EN50131-2-2 Grade 2 certified
- Several European approvals

# VE1012PI

## Vector PIR, 9 curtains, 12 m, Pet Immune

## Technische specificaties

### General

| | |
|---|---|
| Technology | PIR |
| Application type | Vægmontering |
| Anti masking | No |
| Pet immune | Yes |
| Camera | No |
| Signal processing | Vector Verified Enhanced (VE2) |
| Pry-off tamper kit | ST400 (optional) |

### Detection

| | |
|---|---|
| Max. detection range | 12 m |
| Detection range | 12 m |
| Undercrawl protection | Yes |
| Alarm memory | No |
| Alarm time | 3 sek |

### Wired/wireless

| | |
|---|---|
| Wired-wireless | Kablede |

### Inputs/outputs

| | |
|---|---|
| Relay configuration | Isoliert oder 4k7 EOL |
| Remote control lines | Gehtest |

### Physical

| | |
|---|---|
| Colour | Hvid |
| Mounting height | 2,3 bis 3 m |

### Environmental

| | |
|---|---|
| Environment | Indendør |

### Regulatory

| | |
|---|---|
| EN50131 grade | Lønklasse 2 |



Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57