IO950ND

Unidade IO - Montagem DIN Rail - Apollo (SA4700-302)

General

IO950ND is the new DIN-Rail input/output unit which provides supervision of one or more normally open contacts connected to a single pair of cables and a set of changeover relay output contacts.

Ease of Installation

Improved design for ease of wiring meaning faster installation – unit can be fitted to back-box before wiring is connected. Colour coded terminal blocks for easier identification (green for loop wiring, yellow for mains wiring, grey for inputs and low voltage relays).



Detalhes

- Improved design for ease of wiring meaning faster installation
- Loop powered
- Supervise one or more NO switches on a single cable pair
- Local LEDs signalling I/O and fault conditions
- Isolators within each device

IO950ND

Unidade IO - Montagem DIN Rail - Apollo (SA4700-302)

Especificações técnicas

Electrical

Operating voltage	17 to 35 VDC

Physical

Physical dimensions	102 x 33 x 33 mm
Net weight	49 g

Environmental

Operating temperature	-40 to +70°C
Relative humidity	0 to 95% noncondensing
Environment	Indendør

Regulatory

Certification	CPR, EN54-17, EN54-18

Como empresa de inovação, a Kidde Global Solutions reserva o direito de alterar as especificações do produto sem aviso prévio. Para obter informações sobre as especificações mais recentes do produto, visite pt.firesecurityproducts.com online ou contate o departamento comercial.

Last updated on 12 November 2026 - 18:57