FAW350

Conventional VAD, Shallow Base, Wall Mount - Red Flash

General

The FAW350 is a general purpose wall mount LED beacon for fire alarm applications. It features a special base containing all wiring connections and allow for easy removal/placement of the device. With an EN54-23 approved coverage pattern of W-2.4-7.5, each FAW350 may be mounted up to 2.4m high and cover a square room of 7.5 x 7.5m with a single device.

Easy and Fast Installation

The FAx350 beacons allow faster installation and maintenance thanks to an innovative mounting base. Dispensing with the need for locking screws, these beacons use TimeSaver™ bases from the 630 series detectors. Heads are simply locked onto the base with a “twist and click” action, allowing fitting or removal at any time because the base is the only component that needs to be wired. As the cabling requirement is reduced, commissioning time and costs are naturally reduced as well.

Efficient and versatile

The FAx350 beacons utilise a specially designed lens giving a uniformed light output over the specified coverage area. The flash rate of the beacon may be adjusted during installation, with a selection of 0.5Hz or 1Hz.

The mechanism for locking the device to the base may be activated if required. Once activated, a special tool is required to remove the beacon from the base.



Details

- Automatic syncronisation
- Anti-Tamper locking mechanism
- Shallow mouting base
- Wiring directly to base
- Flash rate selectable

FAW350

Conventional VAD, Shallow Base, Wall Mount - Red Flash

Technical specifications

Electrical

Operating voltage	17 to 60 VDC
Current consumption	20 mA @ 0.5 Hz / 40 mA @ 1 Hz

VID

Flash frequency	0.5 or 1 Hz

Physical

Physical dimensions	100 x 81 mm (Ø x D)
Net weight	215 g
Colour	Red
Material	High impact polycarbonate

Environmental

Operating temperature	-25 to +70°C
Relative humidity	5 to 95% noncondensing
Environment	Indoor
IP rating	IP21

Regulatory

Certification	EN54-23

Operation

	Continuous

Automatic synchronisation

	Phased start

Line monitoring input

	Polarised input

Flash color

	Red

EN54-23 rating

Light coverage	W-2.4-7.5
Mounting posistion	Wall
Mounting height	up to 2.4 m
Floor coverage	up to 7.5 x 7.5 m

EN54-23 Coverage: W–2.4-7.5



KIDDE GLOBAL SOLUTIONS

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 16 October 2026 - 11:47