KZ705

KILSEN KC700 / KA700 series standard point detector base

General

The KZ705 is a 5 contact universal detector base for use with the KL700 and KL700A series detectors from Kilsen. In addition to the normal base and remote indication connectors, the KZ705 also has an additional earth terminal connector to allow for easy terminations of a possible cable screen. It allows for cable entry both from behind as well as from the side.

Installation Options

Even though the KZ705 supports surface mount options with cable entry from the side, situations may arise where conduit entry into the base is required. For such applications a surface mount accessory (S700) is optionally available.



Details

- Universal base for both conventional and addressable detectors
- Additional screen/earth terminal available
- Remote indicator support
- Supports rear and side cable entry

KZ705

KILSEN KC700 / KA700 series standard point detector base

Technical specifications

Electrical

Operating voltage	-0

Physical

Physical dimensions	100 x 29 mm (Ø x h)
Net weight	69 g
Mounting type	Ceiling mount

Environmental

Operating temperature	-10 to +70°C
Storage temperature	-10 to +70°C
Relative humidity	10 to 95% noncondensing
Environment	Indoor

Compatible products

Category	Reference	Description
Detection device	KE-DBA-ADPW-KIL	Intelligent addressable base accessory - Kilsen adapter (White)
Detection device	KL731A	KILSEN KA700 Series addressable optical smoke detector
Detection device	KL735A	KILSEN KA700 Series addressable multisensor
Detection device	S700	KC700 / KA700 Series surface mount base accessory
Notification device	PA25/3L	Conventional remote indicator

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 6 October 2026 - 9:33