# SC-51-0100-0001-06

## SmartCell Fire Manual Call Point - Sweden

### Overview

The SmartCell Call Point is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include a protective transparent cover, bidirectional 868 MHz communication, fire indication LED and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.




### Details

- Quick and easy to install
- Compact enclosure
- Includes protective transparent cover
- Unique design
- Inbuilt locking mechanism

# SC-51-0100-0001-06

## SmartCell Fire Manual Call Point - Sweden

## Technical specifications

### General

| | |
|---|---|
| Status indication | LED |
| Wireless frequency | 868 MHz |
| Compatibility | SmartCell, Excellence Gateway |

### Electrical

| | |
|---|---|
| Batteries | 2 x 3.6 V lithium thionyl chloride batteries<br>Fanso: ER14505M<br>HCB: ER14505M (HCB-JS-TZ-02-547) |

### Physical

| | |
|---|---|
| Physical dimensions | 92 x 97 x 47 mm (W x H x D) |
| Net weight | 0.2 kg |
| Colour | Red |
| Mounting type | Wall mount |

### Environmental

| | |
|---|---|
| Operating temperature | -10 to +55°C |
| Storage temperature | -10 to +55°C (without batteries) |
| Relative humidity | 95% noncondensing max. |
| Environment | Indoor |

### Regulatory

| | |
|---|---|
| Compliancy | CE |
| Certification | CPR |
| Standards | EN54-11<br>EN54-13<br>EN54-25 |

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 23 January 2026 - 18:47