# KE-AS3011W

## Sirena/Indicador visual direccionable inteligente Serie Excellence

### General

The innovative Excellence range of intelligent addressable devices offers advanced features for reliability and peace of mind. Coupled with features for ease of installation and maintenance on new fire detection systems, it's a perfect match for exceptional overall performance.

The KE-AS3011W is a WHITE bodied, sounder & visual indicator (VID) for Excellence series fire systems. They are connected over a 2-wire loop and are loop powered. They are compatible with automatic synchronisation controlled from the CIE (control panel).

### Installation

For ease of system planning, Excellence notification devices share a first fix base with Excellence point detectors. This allows for standardised cabling with less cabling issues, and allows devices to be interchanged without rewiring should requirements change. Optional installation accessories to support surface conduit entry, trim skirts address tags and address labels are available to suit multiple applications.

To assist with the installation and commissioning process, a multitude of features ensure that the device is easily and properly inserted into the base, securely connected to the loop and that it functions perfectly. Local multi-coloured LED indicators help visualise any problems locally without requiring access to the fire panel.

### Configuration & Operation

All functional programming is controlled from the CIE and can be changed on the fly without access to the device.

Should the loop be heavily loaded, all Excellence notification devices offer a unique "Battery assisted activation" feature allowing the device to draw its activation power from 3 x CR123 batteries that may be optionally fitted to the device. Using batteries protects the device loop from possible overload which may put the system at risk, and allows for as many as 128 notification devices to be fitted to any Excellence loop. When batteries are used they are automatically supervised buy the device, with ample warning time when batteries require replacing. Under standard operating conditions batteries should provide more than 5 years of support without requiring replacement.

### Safety & Security

Automatic daily self testing ensures that when the device is activated, everything works as expected. Pre-activation self testing ensures that a warning is raised before an event takes place, minimising the risk when notification is required. With the integrated isolator, continuity of operation is ensured even with a single short circuit on the loop.




### Detalles

- Base de primera fijación estándar compartida con detectores puntuales para facilitar la planificación, la logística y la instalación
- Bloqueo de base, etiqueta de dirección, faldón de ajuste y soporte de cableado de superficie para una fácil instalación en todas las condiciones
- Alimentado por lazo con activación asistida por batería que permite hasta 128 dispositivos por lazo
- 32 tonos seleccionables en 4 niveles de volumen seleccionables que se pueden reconfigurar desde el ECI
- Indicación visual integrada de alto brillo para llamar la atención en áreas ruidosas
- Soporte de evacuación en múltiples etapas para flexibilidad de aplicaciones
- Sincronización automática
- Indicador LED de diagnóstico tricolor para una rápida puesta en marcha y asistencia en la detección de fallos

# KE-AS3011W

## Sirena/Indicador visual direccionable inteligente Serie Excellence

## Especificaciones técnicas

### General

| | |
|---|---|
| Compatibility | Sistemas Excellence de Kidde commercial |
| Addressing method | DIL switch |
| Monitoring | Activated, Battery level, Continuously self-checking, Fault |

### Electrical

| | |
|---|---|
| Power supply type | Batteries, Loop powered |
| Batteries | 3 x CR123 (opcional) |
| Operating voltage | 17 a 29 VDC |
| Communication voltage | 4 a 11 V pulsada |
| Current consumption | 250 µA (Reposo)<br>Consulte la hoja de instalación para conocer los valores de corriente de alarma (según la configuración) |

### Sounder

| | |
|---|---|
| Output level | 55 a 102 dB(A) - Depende del tono |
| Output level adjustment | 4 niveles |
| Frequency | Seleccionable por el usuario |
| Selectable tones | 32 |
| Synchronization | Soportado |
| No. of stages | 3 |

### VID

| | |
|---|---|
| Colour | Rojo |
| Flash frequency | 0.5 Hz (1 flash cada 2 s) |
| Synchronization | Soportado |

### Physical

| | |
|---|---|
| Physical dimensions | 111 x 81 mm (Ø x H) |
| Net weight | 300 g |
| Colour | Traffic white (RAL9016) |
| Mounting type | Base mount |
| Mounting position | Ceiling, Wall |
| Material | PC / ABS |

### Environmental


| | |
|---|---|
| Operating temperature | -10 a +55°C |
| Storage temperature | -25 a +70°C |
| Environment | Indoor |
| IP rating | IP21C |

### Regulatory

| | |
|---|---|
| Compliancy | CE, REACH, RoHS 3, WEEE |
| Certification | CPR |

### Productos compatibles

| Categoría | Referencia | Descripción |
|---|---|---|
| Detection device | KE-ASA-AUXW | Accesorio de notificación direccionable inteligente - base profunda (blanco) |
| Detection device | KE-DB3010W | Accesorio detector inteligente serie Excellence - base estándar |




KIDDE COMMERCIAL

Como empresa innovadora, Kidde Global Solutions se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 12 November 2026 - 18:57