
2010-2-UC240-KIT

Comunicatore di allarme UltraSync Kit con IP e doppio percorso 4G / 2G (include custodia e cavi di collegamento).

Overview

UC240 UltraSync communicator is a dual path alarm signalling unit for transmitting alarm signals from a customer's alarm panel to a Central Monitoring Stations (CMS). The monitoring path is based on IP and SIM 4G/2G mobile technology. The unit is designed for use in both security and fire systems.

• Dual-path monitoring for low, medium and high risk sites, covering intruder applications, fire and more.
• These monitored alarm signalling devices are small enough to fit inside most alarm panels. They use two signalling paths – if the primary path is down, the secondary path kicks in. And if that happens, the secondary path will use the primary path reporting and polling times.
• The primary path uses IP technology to send alarm signals over the customer's network or broadband hub.
• The secondary path uses 4G or 2G mobile connectivity – with dual SIMs for extra resilience.
• EN50131 Grade 3 and EN50136 certified for intrusion systems.
• EN54-21 certified for fire alarm systems.



Alarm panel interfaces

• 16 general purpose alarm inputs (Logic High = +2 to +30 V / Logic Low = <1.3 V)
• 3 relay outputs
• Unconnected state: Logic Low
• Standard screw terminals
• Programmable function output-for remote control of site devices
• Line fault output-for status indication at site of alarm signalling path
• Dial Capture with phone line simulation
• Onboard RS232 or RS485 for direct panel interface to some panels

Dial Capture features

• Converts dialler alarm systems into high security signalling devices
• Alarm panel interface supports: Ademco Contact ID, Ademco Hi Speed, Ademco 4+1, Ademco 4+2, SIA 1/2/3

Configuration

• Simple single push button pin learn
• iOS and Android installer app
• Using on board menu driven by push buttons

2010-2-UC240-KIT

Comunicatore di allarme UltraSync Kit con IP e doppio percorso 4G / 2G (include custodia e cavi di collegamento).

Specifiche tecniche

General

Product line	UltraSync

Network

Communicator type	2G, 4G, Cellular, IP

Reporting

Reporting protocols	Contact ID, SIA
Supported receivers	UltraSync

Interfaces

Ethernet	RJ-45 1000 Mbps Ethernet Interface
Antenna	Yes, included

Physical

Colour	Black

Environmental

Environment	EN50130-5 ; Class II - Indoor (general)

Regulatory

Certification	EN50131 Grade 3, EN50136, EN54-21

In quanto azienda in continua innovazione, Kidde Global Solutions si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 12 November 2026 - 18:57