FC-200-003

Pulsante di allarme wireless FUSION (Rosso) con mascherina di protezione

General

The FC-200-003 is an RED addressable, wireless, resettable manual call point including batteries. It is suitable for indoor use and connects to a Fusion or Ziton gateway.

Batteries typically have a minimum of three-year life expectancy.

Overview

The FC-200-003 call point is quick and easy to install and offers individual addressing at the fire control panel. Dual band 868 MHz operation, auto adjusting power output, fire indication LED, resettable element, anti tamper and a test key are standard features. A transparent hinged cover is also included for protection against accidental operation in busy environments.

This device is third party EN certified and compatible with the EMS FireCell system, EMS Fusion Radio Loop Module (RLM), EMS Wireless Zone Monitor (WZM) as well as Ziton ZPR868 series wireless interfaces.

Operating Principle

Fire detection is often required in buildings where cabling presents a challenge because of the design or architecture of the building. Wireless installation provides the ideal solution to these environments.

Ideal for the application in hybrid systems where both wired and wireless devices share the same CIE, up to five gateways may be installed on any wired CIE loop. Up to five gateways can easily be incorporated on a single installation (with larger systems possible through design), using an easy to use, site survey kit to confirm the positioning of the wireless devices. Every gateway supports up to 31 wireless devices.

Every wireless device is assigned an address which is recognised by the control panel in the same way as is the address of any wired device connected directly to the CIE loop wiring.



Dettagli

- Dual band 868 MHz operation
- Fire indication LED
- Resettable element
- Anti tamper locking
- Protective cover
- Third party EN certified

FC-200-003

Pulsante di allarme wireless FUSION (Rosso) con mascherina di protezione

Specifiche tecniche

General

Wireless frequency	868 MHz
Connectivity	Wireless
Addressing method	Electronic

Electrical

Power supply type	Batteries

Detection

Monitoring	Device type, Presence, Tamper

Physical

Colour	Red
Mounting type	Wall mount
Material (body)	ABS

Environmental

Vandal proof	No
Environment	Indoor

Regulatory

Compliancy	CE, REACH, RED (2014/53/EU), RoHS 3, WEEE
Certification	CPR

In quanto azienda in continua innovazione, Kidde Global Solutions si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 12 November 2026 - 18:57