# BS129NS3

**Sealed Lead-Acid Battery, 12 V, 26 Ah, V0 Flame Retardant Case**



# BS129NS3

## Sealed Lead-Acid Battery, 12 V, 26 Ah, V0 Flame Retardant Case

## Technische specificaties

### General

| | |
|---|---|
| Product type | Sealed lead acid battery |

### Electrical Characteristics

| | |
|---|---|
| Nominal voltage | 12 V |
| Nominal capacity | 26 Ah |
| Internal approx. resistance | 10 mOhm |

### Charge / discharge

| | |
|---|---|
| Max. charge voltage | 13.8 VDC at +20°C |
| Max. charge current | 7.8 A |
| Max. discharge current | 130 A |

### Temperature

| | |
|---|---|
| Charging temperature | 0 to +40°C |
| Discharging temperature | -15 to +50°C |

### Physical

| | |
|---|---|
| Material | ABS |
| Terminal type | MS bolt & nuts |

### Environmental

| | |
|---|---|
| Fire retardant | Yes |
| Storage temperature | -15 to +50°C |

### Regulatory

| | |
|---|---|
| Compliancy | CE, RoHS 2, WEEE |
| Certification | NFA2P |

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57