ATS1236

32 zoners 433Mhz trådløs modtager DGP

Increasing zone capacity

The ATS1236 wireless receiver adds wireless capabilities to the Advisor Advanced range of panels.

The wireless DGP supports most of the legacy 433 MHz 63-bit transmitters as well as the new generation of 433 MHz LoNa transmitters of which the wireless communication is fully encrypted, avoiding unauthorized interference. Up to 32 wireless sensors and up to 16 keyfobs can be learned in.

The ATS1236 wireless receiver provides two wired zone inputs and one programmable relay output.

Installation and programming

The wireless DGP needs to be installed outside the panel housing in order to assure a maximum wireless range. The 433MHz wireless solution will monitor the status and presence of each wireless device and will respond in case of an RF jamming condition.

The ATS1236 wireless receiver can be programmed from the keypad as well as from the downloader. The firmware of the module is remotely upgradeable.



Detaljer

- Adds wireless capabilities to Advisor Advanced
- Two wired zone inputs
- One programmable SPDT Form C relay output
- Supports legacy 63-bit 433 MHz and new LoNa 433 MHz transmitters
- Learn-mode technology
- Removable terminals
- EN50131-1/EN50131-3/EN50131-6 Grade 2 Class II (pending) INCERT (pending)
- Firmware upgradeable

ATS1236

32 zoners 433Mhz trådløs modtager DGP

Tekniske specifikationer

General

Expander type	Drahtloser Expander
Product line	Advisor Advanced, Axon
Connection type	Databus connection
Compatibility	Advisor Advanced MR 4.2 or higher

System

Addressing	Dip-Schalter

Inputs

Total	32
No. of wireless zones	32 wireless sensors + 16 keyfobs
Onboard	2 wired

Outputs

Onboard	1
Type of outputs	SPDT Form C relay

Wireless

Operating frequency	433-MHz Ältere Version, 433 MHz LoNa

Electrical

Operating voltage	12Vdc via bus
Current consumption	typical : 47 mA maximum : 51 mA
Integrated power supply	No

Physical

Physical dimensions	155 x 95 x 26 mm
Net weight	0.160 kg
Colour	Weiß
Material	ABS Plastik

Environmental

Operating temperature	-10°C to 55°C
Relative humidity	90% relative humidity non-condensing
Environment	EN50130-5 ; Klasse II - Indoor (allgemein)

Regulatory

Compliancy	CE
Certification	CE, EN50131 Grad 2, INCERT
Standards	EN50131 Grade 2 & INCERT pending

Kidde Global Solutions er et innovativt selskab og forbeholder sig ret til at ændre produktspecifikationer uden varsel. De nyeste produktspecifikationer kan du finde på dk.firesecurityproducts.com eller ved at kontakte din salgsrepræsentant hos.

Last updated on 12 November 2026 - 18:57