# DC120

## Recessed mount contact - stubby press-fit

### Stubby Press Fit Contact

The DC120 magnetic contact is designed specifically for applications where space is limited. The short length makes it ideal for thin framed windows and doors where longer units cannot be used. Press fit ribs on the housing make for quick and easy installation.

### Installation

The hermetically-sealed reed switch is potted using exclusive polyurethane compound. Switch and Alnico V magnet is drill-mounted in wood or aluminium with a suitable adhesive. The switch and magnet housing have three fins to press-fit against the mounting hole.



### Details

- Switch only 19 mm long, ideal for installation in thin framed doors and windows
- With 18 mm gap distance for faster installation
- Ideal for pre-wiring, eliminates forcing switch and pre-wire into same header hole
- Available in different cable lengths
- Tamper loop provided

# DC120

## Recessed mount contact - stubby press-fit

## Technical specifications

### General

| | |
|---|---|
| Application type | Versenkte Montage |
| Contact type | NC |
| Connectivity | 4 wires, 2 m |

### Wired/wireless

| | |
|---|---|
| Wired-wireless | Verdrahtet |
| Operating gap | 18 mm (max.) |

### Physical

| | |
|---|---|
| Dimensions contact / sensor | 9 x 20 mm (Ø x L) |
| Diameter | 10 mm |
| Colour | Beige |

### Regulatory

| | |
|---|---|
| EN50131 grade | Klasse 2 |



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 13 August 2026 - 11:05