# VE735

**PIR met 20m groothoekbereik en 60m longbeam. 9-15VDC. NC en REQ.**



# VE735

## PIR met 20m groothoekbereik en 60m longbeam. 9-15VDC. NC en REQ.

## Technische specificaties

### General

| | |
|---|---|
| Technology | PIR |
| Application type | Wandmontage |
| Anti masking | No |
| Pet immune | No |
| Camera | No |
| Signal processing | Vector Verified Enhanced (VE2) |
| Pry-off tamper kit | On board |

### Detection

| | |
|---|---|
| Max. detection range | 60 m |
| Undercrawl protection | Yes |
| Alarm memory | Yes |
| Alarm time | 3 sek |

### Wired/wireless

| | |
|---|---|
| Wired-wireless | Verdrahtet |

### Inputs/outputs

| | |
|---|---|
| Relay configuration | Isoliert oder 4k7 EOL |
| Remote control lines | Tag/Nacht, Gehtest |

### Electrical

| | |
|---|---|
| Power supply type | 12 VDC |

### Physical


| | |
|---|---|
| Colour | Weiß |
| Mounting height | 1,8 bis 3 m |

### Environmental

| | |
|---|---|
| Environment | Drinnen |

### Regulatory

| | |
|---|---|
| EN50131 grade | Klasse 2 |
| Certification | VdS |




Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar nl.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57