ATS1140

7" ekran dotykowy do systemów Everon oraz Advisor Advanced z wbudowanym czytnikiem Mifare EV1-EV3. Możliwość pracy w trybie secure mode, zgodny z Grade 3.

At a glance

The Advisor Advanced product family has a new addition: the ATS1140 graphical touchscreen. This device offers simple fingertip control of the security system with a 7-inch high-responsive touchscreen display that features easy-to-understand graphics. The ATS1140 is designed to perfectly complement other control units in the Advisor Advance security system family, ensuring a smooth user experience.

The ATS1140 boasts a modern design with a new graphical user interface that features icon-based and readable text. The display's contrast and the built-in buzzer's volume level can be adjusted via the configuration board. This device also comes with a simplified and intuitive graphical user interface, allowing users to easily navigate the programming, operational features, dashboard, system status, alarms, logs, and additional function keys.

Overall, the ATS1140 graphical touchscreen combines functionality and style to provide an efficient and user-friendly experience.



Built-in secure card reader

The ATS1140 is equipped with a Mifare Desfire EV1/EV2/EV3 card reader that is built-in. When the device is in secure mode, the data is encrypted from the card to the keypad and from the keypad to the Advisor Advanced control panel.

The ATS1140 can be used for arming/disarming the system with the PIN code, the card or a combination of both for enhanced security. It works with the multiple card badging solutions that are available in the Advisor Advanced product family.
Alarm system activation: a user can turn on the alarm system by badging their card three times within a 10-second interval.
Door access control: doors can be programmed for specific behaviors based on badging with the card. For example, with a single badge scan, granting seamless entry and exit without requiring a card, and a triple badge scan will promptly re-lock the door, providing enhanced convenience for the end user.

Quick access

The touch display menus are thoughtfully organized, featuring a clean and intuitive design that makes navigation a breeze. The single-touch operation eliminates the need for complex maneuvers, allowing for effortless interaction with the system. Whether you are an advanced tech user or a novice, you will find the touch display menus to be user-friendly and highly accessible.

Szyba i Prosta Instalacja

Montaż jest niezwykle prosty, należy rozdzielić tył obudowy od ekranu, zamontować ja na ścianie, podłączyć okablowanie i wcisnąć wyświetlacz z powrotem w obudowę, w taki sposób nie trzeba martwić

Szczegóły

- Elegancki, nowoczesny wygląd
- Uproszczony i intuicyjny graficzny interfejs użytkownika
- Kolorowy 7" wyświetlacz dotykowy
- Możliwość wgrania własnego logo
- Wygodne, programowalne klawisze funkcyjne
- Wbudowany czytnik Mifare Desfire EV1/EV2/EV3
- Konfigurowalny wyświetlacz LCD, brzęczyk i podświetlenie klawiszy
- Zgodny z kartami ATS145x lub innymi (z wyjątkiem ATS1458)
- Intuicyjny interfejs użytkownika oparty na ikonach
- Wsparcie wielu języków
- Funkcja wirtualnej klawiatury

się czy ekran jest odpowiednio zabezpieczony.
W celu podłączenia ATS1140 do centrali Advisor Advanced należy upewnić się że panel posiada wgrane oprogramowanie w wersji MR4.10 lub nowsze, a w przypadku systemu Everon MR3.1 lub nowsze oraz sam wyświetlacz musi posiadać firmware FW2.0.5 lub nowszy. W razie pytań należy skontaktować się z lokalnym wsparciem technicznym.

ATS1140

7" ekran dotykowy do systemów Everon oraz Advisor Advanced z wbudowanym czytnikiem Mifare EV1-EV3. Możliwość pracy w trybie secure mode, zgodny z Grade 3.

Specyfikacja techniczna

General

User interface	Berührungssensitive Tasten
Product line	Advisor Advanced, Everon
Status LEDs	1
Integrated reader	Sicheres MIFARE
Language	Multi-language support
Supported Firmware	MR4.10 or later

System

Function keys	3
Supported card types	MIFARE® Classic UID, MIFARE® DESFire® EV1, MIFARE® DESFire® EV2, MIFARE® DESFire® EV3
Addressing type	Softwareadressierung
Supported cable type	WCAT 52/54 lub odpowiednik

Communication

Communication type	Verdrahtet
Reading distance	Do 3 cm
Wiring	RS-485, 4-wire bus
Connected per data bus	8 per data bus max 16 per system

Inputs/Outputs

Inputs	1
Input type	RTE (NO)
Outputs	1
Output type	Otwarty kolektor(OC), 100 mA max, 15 VDC max.

Electrical

Operating voltage	12.0 do 13.5 VDC (zasilanie z centrali)
Current consumption	330 mA dla 13.7 VDC, 375 mA dla 12 VDC (max.) 220 mA dla 13.7 VDC, 250 mA dla 12 VDC (średnio) 70 mA dla 13.7 VDC, 80 mA dla 12 VDC (tryb czuwania)

Physical

Physical dimensions	127 x 179 x 20 mm
Net weight	460 g
Colour	Weiß
Mounting type	Wandmontage
Material	ABS Plastik

Environmental

Operating temperature	0 do +50°C
Relative humidity	do 95% bez kondensacji
Environment	Drinnen
IP rating	IP30 IK06

Regulatory

Certification	EN50131 Grad 3, F&P, FG, IMQ, INCERT, NFA2P, SBSC

Wyroby zgodne

Kategoria	Odniesienie	Opis
Control Panel	ATS1700-MM	Centrala alarmowa Everon 1700, wbudowane IP, certyfikacja GRADE 3, WebApp, 8 wbudowanych linii z możliwością rozszerzenia do 48, 4 obszary, w średniej metalowej obudowie
Control Panel	ATS3700-MM	Centrala alarmowa Everon 3700, wbudowane IP, certyfikacja GRADE 3, WebApp, 16 wbudowanych linii z możliwością rozszerzenia do 256, 16 obszarów, w średniej metalowej obudowie
Control Panel	ATS4700-LM	Centrala alarmowa Everon 4700 w dużej obudowie
Control Panel	ATS4700-MM	Centrala alarmowa Everon 4700, wbudowane IP, certyfikacja GRADE 3, WebApp, 16 wbudowanych linii z możliwością rozszerzenia do 1000, 64 obszary, w średniej metalowej obudowie

Będąc firmą innowacyjną, Kidde Global Solutions zastrzega sobie prawo do zmian w specyfikacji wyrobów bez uprzedzenia. W celu uzyskania najnowszych specyfikacji prosimy o wizytę na stronach pl/firesecurityproducts.com lub kontakt z przedstawicielem handlowym.

Last updated on 12 November 2026 - 18:57