2010-2-UC240-KIT

UC240 Kit FÖR BRANDLARM (incl. enclosure, IO cable w/ EOL, serial cable accessories) for fire panel, UltraSync communicator with IP and 4G/2G dual path suitable

Overview

UC240 UltraSync communicator is a dual path alarm signalling unit for transmitting alarm signals from a customer's alarm panel to a Central Monitoring Stations (CMS). The monitoring path is based on IP and SIM 4G/2G mobile technology. The unit is designed for use in both security and fire systems.

- Dual-path monitoring for low, medium and high risk sites, covering intruder applications, fire and more.
- These monitored alarm signalling devices are small enough to fit inside most alarm panels. They use two signalling paths – if the primary path is down, the secondary path kicks in. And if that happens, the secondary path will use the primary path reporting and polling times.
- The primary path uses IP technology to send alarm signals over the customer's network or broadband hub.
- The secondary path uses 4G or 2G mobile connectivity – with dual SIMs for extra resilience.
- EN50131 Grade 3 and EN50136 certified for intrusion systems.
- EN54-21 certified for fire alarm systems.









Alarm panel interfaces

- 16 general purpose alarm inputs (Logic High = +2 to +30 V / Logic Low = <1.3 V)
- 3 relay outputs
- Unconnected state: Logic Low
- Standard screw terminals
- Programmable function output-for remote control of site devices
- Line fault output-for status indication at site of alarm signalling path
- Dial Capture with phone line simulation
- Onboard RS232 or RS485 for direct panel interface to some panels

Dial Capture features

- Converts dialler alarm systems into high security signalling devices
- Alarm panel interface supports: Ademco Contact ID, Ademco Hi Speed, Ademco 4+1, Ademco 4+2, SIA 1/2/3

Configuration

- Simple single push button pin learn
- iOS and Android installer app
- Using on board menu driven by push buttons

2010-2-UC240-KIT

UC240 Kit FÖR BRANDLARM (incl. enclosure, IO cable w/ EOL, serial cable accessories) for fire panel, UltraSync communicator with IP and 4G/2G dual path suitable

Tekniska specifikationer

General

Product line	UltraSync

Network

Communicator type	2G, 4G, Cellular, IP
GSM frequency	LTE: Penta-Band 700 (Bd28) / 800 (Bd20) / 900 (Bd8) / 1800 (Bd3) / 2100 MHz (Bd1) + GPRS Dual band (900/1800 MHz)

Reporting

Reporting protocols	Contact ID, SIA
Supported receivers	UltraSync

Interfaces

Ethernet	RJ-45 1000 Mbps Ethernet Interface
Antenna	Yes, included

Input/Output

Inputs	16 general purpose alarm inputs
Outputs	3 relay outputs

Electrical

Operating voltage	9.5 to 30 VDC
Current consumption	85mA @12 VDC, 185mA @24 VDC (Maximum loading) 45mA @12 VDC, 100mA @24 VDC (Normal operation)

Physical

Physical dimensions	95 x 67 x 17 mm
Colour	Black

Environmental

Operating temperature	-10 to +55°C
Relative humidity	5 to 75%
Environment	EN50130-5 ; Class II - Indoor (general)

Regulatory

Certification	EN50131 Grade 3, EN50136, EN54-21

KIDDE COMMERCIAL

Kidde Global Solutions förbehåller sig rätten att ändra produktspecifikationer utan föregående meddelande. För de senaste produktspecifikationerna, besök se.firesecurityproducts.com online eller kontakta din försäljningsrepresentant.

Last updated on 12 November 2026 - 18:57