BS129N

Battery, 12 V, 26 Ah

Product overview

Sealed Lead Acid battery 12 V / 26 Ah with MS bolt & nuts terminal type.



Details

- Maintenance free
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechangeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

BS129N
Battery, 12 V, 26 Ah

Technical specifications

General

Product type	Forseglet blybatteri

Electrical Characteristics

Nominal voltage	12 V
Nominal capacity	26 Ah
Internal approx. resistance	10 mOhm

Charge / discharge

Max. charge voltage	13.8 VDC @ +20°C
Max. charge current	7.8 A
Max. discharge current	130 A

Temperature

Charging temperature	0 to +40°C
Discharging temperature	-15 to +50°C

Physical

Physical dimensions	166 x 175 x 125 mm
Net weight	9.528 kg
Shipping weight	9.528 kg
Colour	Mørkegrå
Material	ABS
Terminal type	MS bolt & nuts

Environmental

Fire retardant	No
Vandal proof	No
Operating temperature	0 to +40°C
Storage temperature	-15 to +50°C

Regulatory

Compliancy	CE, RoHS 2, WEEE
Certification	VdS

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 6 March 2026 - 13:50