AS505

Outdoor siren with single amber beacon



Details

- Attractive high quality shaped housing
- Double piezo sounder with 114 dB @ 1m sound output
- Vertical or horizontal mounting
- Fully potted electronics
- Strobe flash light
- Selectable comfort LED indication
- Pry-off and opening tamper detection
- Self detection of cable cutting or tampering
- Installer friendly
- Hold-off polarity selection
- Independently hold-off for both beacon and siren
- A choice of cut off time
- Selectable tamper configuration

AS505

Outdoor siren with single amber beacon

Technical specifications

General

Accessory group	Sirene
Type	Udendørs sirene
Sounder output (dB @ distance)	114 dB at 1 m (typical)
PCB protection	Fully potted
Tamper & pry-off	Yes
Cut-off timer	3 min, 5 min, 10 min, 20 min
Comfort LED	Yes
Sounder	Double piezo
Low voltage detection	Yes
Metal inner cover	Optional

Flash specifications

Flash frequency	50 to 60 flashes/min

Electrical

Operating voltage	10 to 14.5 VDC
Current consumption	350 mA 40 mA (standby, with NiCd battery) 20 mA (standby, without battery)

Physical

Physical dimensions	212 x 300 x 55 mm
Material	Polycarbonat
Material (housing	Polycarbonate (3 mm)

Environmental

Operating temperature	-25 to +55°C
IP rating	IP54

Frequency

	0.5 to 3 kHz

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 16 June 2026 - 15:23