AS964I

Röd siren med hög sockel, inbyggd isolator. 3 toner, IP65, 100 dB(A) +/- 3 dB, 17-28 VDC, 310 µA-5,1mA

General

The AS964I is a 950 series, intelligent loop powered open-area sounder in RED with a built in isolator. It is designed for use in indoor and outdoor open area applications. It supports 3 tones with two volume settings.

A locking mechanism is available to prevent unauthorized removal of the AS964I from its base.

Isolation and Maintenance

The AS964I sounder is supplied with an isolating base. A yellow LED on the base is illuminated if a loop short circuit is detected. All fault and abnormal conditions such as sounder failures are reported back to the panel for easy faultfinding.

Sounder Tone Support

That AS964I supports the following tones:

·Standard
·Slow Whoop (NEN2575)
·DIN (33404pt3)

Two volume settings are available in each tone variant.



Detaljer

- Self-test fault monitoring
- Multiple tones
- Alarm synchronisation
- Loop powered
- Including loop isolator

AS964I

Röd siren med hög sockel, inbyggd isolator. 3 toner, IP65, 100 dB(A) +/- 3 dB, 17-28 VDC, 310 µA-5,1mA

Tekniska specifikationer

Environmental

Environment	Indendør

Regulatory

Certification	EN54-17, EN54-3

Kidde Global Solutions förbehåller sig rätten att ändra produktspecifikationer utan föregående meddelande. För de senaste produktspecifikationerna, besök se.firesecurityproducts.com online eller kontakta din försäljningsrepresentant.

Last updated on 12 November 2026 - 18:57