GS960AM

Akustisk glasbrudsdetektor med Antimask, Reg. F&P kl. 3.

General

GS960AM is an acoustic glass break detector which gives an alarm when glass is smashed at intrusion attempts through windows, doors and glazed walls. It uses an advanced micro-controller technology which is programmed to take a lot of relevant acoustic factors into account. Using the Digital Room Compensation the detector can distinguish between a true glass break and other irrelevant sounds. In parallel the design of the detector makes it suitable for wall or ceiling mount as long as the detector has a free “line-of-sight” to the window being protected. This sensor will detect the breaking of different types of glass panes like single glazed (float and tempered), double glazed (float and tempered), double glazed where the inner pane is covered with security film, triple glazed (float and tempered) and laminated glass pane. GS960AM is equipped with an AM function, a separate relay, which gives an alarm at sabotage of microphone. When sealing the microphone completely with elastic material like e.g. chewing gum or isolation tape it will be detected. When removing those materials the sensors will get back to its normal state.

Connection to a 24-hour loop

The sensor is constructed for continuous detection, is extra resistant to different acoustic disturbances and works well in most environments. In environments with very high rates of disturbances like e.g. industrial workshops or gyms, the oKGSome of a four week test period will help to decide whether to use the detector in a 24 hour loop.

Special tools and accessories

The GS960-TR tester is a specially developed tool for calibrating and adjusting the GS960 for optimal function in the acoustic space – the DRC Digital Room Compensation procedure. Using this tool to test the detector settings you do not need to open it again as the tester will communicate with the detector acoustically. There is also an additional accessory GS960-RB which is a plug-in EOL resistor board allowing to easily integrate GS960AM into an existing Advisor Advanced system without the hassle of adding EOL resistors.



Detaljer

- Protection of multiple windows in a room
- Maximum detection range up to nine meters
- 24 h supervision set-up possible
- Detect glass breaking up to triple panes
- Separate accessory for proper set-up and testing available
- 24/7 internal self-test procedure
- Detects the masking of the microphone
- Holding several European security approvals

GS960AM

Akustisk glasbrudsdetektor med Antimask, Reg. F&P kl. 3.

Tekniske specifikationer

General

Technology	Acoustic
Glass types	Lamineret, Hærdet
Range	9m radius at 165°
Relay output	50 mA, 50 V DC / peak AC, Rs ≤ 30 Ω
Tamper switch	Yes

Wired/wireless

Wired-wireless	Kablede

Electrical

Current consumption	12 mA at 12 V, 7.3 mA at 24 V at quiescent state

Physical

Physical dimensions	68 x 109 x 40 mm
Net weight	103
Shipping weight	130
Colour	Hvid
Material	ABS plast
Mounting type	Loftmontering, Vægmontering

Environmental

Operating temperature	+5 to 40°C
Relative humidity	Max. 93% RH
Environment	Indendør

Regulatory

Certification	VdS

Kidde Global Solutions er et innovativt selskab og forbeholder sig ret til at ændre produktspecifikationer uden varsel. De nyeste produktspecifikationer kan du finde på dk.firesecurityproducts.com eller ved at kontakte din salgsrepræsentant hos.

Last updated on 12 November 2026 - 18:57