ACL875SU-S

ACL800 Tastatur - freistehend, Aufputzmontage, Silber

Product description

ACL875SU range is a standalone digital keypad for access control applications with backlight keys, 99 user codes, 2 outputs (relay and transistor) and 1 push button input. These keypads are available in three different color finishes. Authorized users can be assigned specific codes for use in access control applications, electrical switching and arming/disarming alarm systems. The Users can be assigned to activate the first, the second or both outputs. There is a 30 seconds lockout after 8 successive invalid PIN Codes. The tamper switch output can trigger the alarm system, if an attempt is made to open or remove the unit from the wall.

The ACL800 range

ACL875SU range is a standalone digital keypad for access control applications with backlight keys, 99 user codes, 2 outputs (relay and transistor) and 1 push button input. These keypads are available in three different color finishes. Authorized users can be assigned specific codes for use in access control applications, electrical switching and arming/disarming alarm systems. The Users can be assigned to activate the first, the second or both outputs. There is a 30 seconds lockout after 8 successive invalid PIN Codes. The tamper switch output can trigger the alarm system, if an attempt is made to open or remove the unit from the wall.



Einzelheiten

- Innen/Außenbereich
- Staubgeschützt und wasserdicht (IP65)
- Bis zu 99 Benutzercodes
- Codes können 1 bis 8 Stellen lang sein
- Attraktives und zeitloses Design
- Enthält einen Summer
- Dreifarbige LED's
- Aufputzmontage
- Hintergrundbeleuchtung
- Tastenfeld

ACL875SU-S

ACL800 Tastatur - freistehend, Aufputzmontage, Silber

Technische Spezifikationen

System

Max. reader distance to panel	50 m
RTE (Request To Exit)	No
CSN (Card Serial Number)	No
Custom data model	No
No. of LEDs	3
No. of covers included	1

Technology

Reader type	PIN keypad
Read write	No
SAM module embedded	No

Interface & connections

Interface	Wiegand
Connector type	Pigtail
Pigtail length	100 cm

Tamper type

Pry-off tamper	No
Opening tamper	Yes

Operation

Stand-alone	Yes
Stand-alone no. of users	99
PIN keypad	Yes
PIN length	1 bis 8 Ziffern

Electrical

Power supply type	VDC
Power supply value	12-24 VDC; 15-24 VAC
Current consumption	60mA @ 12 VDC

Physical

Physical dimensions	92 x 51 x 25 mm
Net weight	173 g
Shipping weight	305 g
Colour	Silver
Material	Moulded aluminium
Form factor	Mullion
Mounting type	Surface mount

Environmental

Environment	Indoor, Outdoor
Storage temperature	-20 bis +50°C

Regulatory

Compliancy	CE, RoHS

Betrieb

Tasten	Metallisch beleuchtet
Mastercode für die Programmierung	1
Benutzer-Codes	99
Grüne LED	Status von Ausgang 1
Rote LED	Status von Ausgang 2
Orangene LED	Programmierstatus und Tastendruck
Tastatursperre	Sperrung für 30 Sekunden mit Signalton nach 8 aufeinanderfolgenden falschen Codes
Summer	1

Technologie

Ausgänge	1 Relais (2A) & 1 Transistor (250mA)
Relais-Zeit	Selbsthaltend oder zeitgesteuert von 1 bis 99 Sekunden
Speicher	EEPROM (die Programmierung ist auch bei Stromausfall sicher)

Manipulationstyp

Manipulationsschutz	In geöffnetem oder demontiertem Zustand

Als innovatives Unternehmen behält sich Kidde Global Solutions das Recht vor, Produktspezifikationen ohne Ankündigungen zu ändern. Für die aktuellsten Produktspezifikationen, besuchen Sie bitte de.firesecurityproducts.com online oder kontaktieren Sie bitte unsere Vertriebsmitarbeiter.