SH-32-0220-0001-99

SmartCell White Sounder and Wall-Beacon (VAD White Flash)

Overview

The SmartCell Sounder Beacon is quick and easy to install and offers individual addressing at the Excellence Control Panel or Gateway.

Features include an EN54:23 certified VAD, 32 sounder tones, bidirectional 868 MHz communication and an anti-tamper locking mechanism.

This device is third party certified and compatible with the Excellence wireless gateway.



Details

- Fully wireless
- Quick and easy to install
- EN54:23 certified visual alarm device (VAD)
- 32 sounder tones
- Unique design
- Inbuilt locking mechanism

SH-32-0220-0001-99

SmartCell White Sounder and Wall-Beacon (VAD White Flash)

Technical specifications

General

Wireless frequency	868 MHz
Compatibility	Excellence Gateway

Electrical

Batteries	3 x 3.6 V lithium thionyl chloride batteries. Fanso: ER14505M HCB: ER14505M (HCB-JS-TZ-02-547)

Sounder

Output level	95 dB(A) at 1 m max.
Output level adjustment	High or low
Selectable tones	32

VAD

Colour	white flash
Rating	W-2.4-6
Flash frequency	0.5 Hz (1 flash, every 2 seconds)

Physical

Physical dimensions	110 x 77 mm (Ø x D)
Net weight	0.2 kg
Colour	White
Mounting type	Wall mount
Mounting position	Wall

Environmental

Operating temperature	-10 to +55°C
Storage temperature	-10 to +30°C (with batteries) -10 to +55°C (without batteries)
Relative humidity	95% noncondensing max.
IP rating	Type B: for indoor/outdoor use (IP33)

Regulatory

Compliancy	CE, REACH, RED (2014/53/EU), RoHS 3, WEEE
Certification	CPR
Standards	EN54-3 EN54-13 EN54-23 EN54-25

Compatible products

Category	Reference	Description
Batteries	SH-836-000	AA ER14505M 3.6V Lithium Battery
Interface unit	SH-14-3201-000 1-99	Excellence SmartCell Addressable Wireless Gateway
Test Equipment	SH-21-BASE-020 0	SmartCell Device / Sounder base – White (10 pack)

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 24 April 2026 - 14:14