PB511

AIR Line Detector, 2 Lines, 40 m Outdoors, 80 m Indoors



Details

- Range 40/80 metres
- Indoor and outdoor installation
- 2 Synchronised lines
- 4 Optional frequency steps ensure that one receiver will only 'see' one transmitter
- Adjustable precision optics
- Immune to external light
- High protection against EMC noise
- AGC sensitivity control
- Extra lens heater available as an accessory
- Full range of tower accessories for outdoor fitting

PB511

AIR Line Detector, 2 Lines, 40 m Outdoors, 80 m Indoors

Technical specifications

General

Category	Aktive Infrarøde Stråler
Product type	Aktiv Infrarød Stråle
Infrared system	2-beam LED, double frequency modulation
Tamper	NC, max. charge 30 VAC/VDC, 100 mA

Detection

Range	40 / 80 m (outdoor / indoor)
Alarm response time	50 to 700 ms

Inputs/outputs

Alarm output	NC/NO, max. charge 30 VAC/VDC, 0.5 mA

Electrical

Power supply value	12 to 30 VDC
Current consumption	105 mA (Alarm) 75 mA (Normal)

Physical

Physical dimensions	72 x 72 x 170 mm
Net weight	380 g
Colour	Sort
Material	Polycarbonat

Environmental

Operating temperature	-25 to +60°C
Environment	Udendørs

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 25 August 2026 - 13:47