DT657L

Apollo Series 65 Heat Detector, Class CS With Blinking LED (55000-136)

General

The 650 Series conventional detectors are designed for the highest effectiveness utilising the latest technology. A wide operating voltage (9 to 33 VDC) allows them to be used on any security system.

Ionisation Detectors

The detector sensor consists of 2 cambers - an open outer chamber and a semi-sealed reference chamber. As smoke enters the open chamber, the voltage difference between the chambers is measured and compared to a pre-set trigger level for alarm. An integrating ionisation detector, suitable for use in areas where transient levels of smoke may be present, is also available.

Optical Smoke Detectors

These detectors use a pulsing LED and photo diode in an dark optical chamber. In the event of smoke from a fire entering the chamber, the light from the LED is scattered and registered by the photo diode.

Series 650 Heat Detectors

Heat detectors normally use a matched pair of thermistors (one exposed and one sealed) to sense heat. In case of fire, the exposed thermistor's temperture increases rapidly, causing the detector to change into the alarm state becuase of the imbalance. Rate-of-rise algorythms may detect the fire as the temperature increases, but a fixed upper temperture limit will force the detector into alarm if the rate of temperature increase has been too slow. The static only response heat detectors use only one thermistor and changes to the alarm state at a preset temperature.

Standard Base

The base enables detectors to be plugged in without any need for force - particularly useful when fitting to suspended ceilings. The base has a "one way only" fit and are lockable. They contain no electronic parts that could be damaged during installation. The detectors are polarity insensitive and bases are easy to wire with an earth connector.



Details

- Advanced electronic technology
- Flashing LED option on selected units
- Polarity insensitive
- Common base
- Elegant slim-line design
- EN54 approved
- Proven detection performance
- May be used on security systems
- Wide range of bases available

DT657L

Apollo Series 65 Heat Detector, Class CS With Blinking LED (55000-136)

Technical specifications

General

Status indication	Red LED (Alarm)

Electrical

Operating voltage	9 to 33 VDC
Current consumption	55 µA @ 24 VDC (Quiescent) 52 mA @ 24 VDC (Alarm) 50 µA @ 9VDC (Quiescent) 17 mA @ 9 VDC (Alarm)

Physical

Physical dimensions	42 x 100 mm (H x Ø)
Mounting type	Assemblage sur socle

Environmental

Operating temperature	-20 to +90°C (no icing)
Relative humidity	0 to 95% noncondensing
Environment	Indendør
IP rating	IP54
Max. wind	Not affected

Regulatory

Certification	EN54-5

Remote alarm output current

	17 mA

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 14 March 2025 - 12:47