PB521

Arix set AIR, met 2 beams voor gebruik binnen max. 120 meter of gebruik buiten max. 60 meter.



Details

- Range 60/120 metres
- Indoor and outdoor installation
- 2 synchronised lines
- 4 optional frequency steps ensure that one receiver will only 'see' one transmitter
- Adjustable precision optics
- Immune to external light
- High protection against EMC noise
- AGC sensitivity control
- Extra lens heater available as an accessory
- Full range of tower accessories for outdoor fitting

PB521

Arix set AIR, met 2 beams voor gebruik binnen max. 120 meter of gebruik buiten max. 60 meter.

Technische specificaties

General

Category	Aktive Infrarøde Stråler
Product type	Aktiv Infrarød Stråle
Infrared system	2-beam LED, double frequency modulation
Tamper	NC (max. charge 30 VAC/VDC - 100 mA)

Detection

Range	60 / 120 m (outdoor / indoor)
Alarm response time	50 to 700 ms

Inputs/outputs

Alarm output	NC/NO (max. charge 30 VAC/VDC - 0.5 mA)

Electrical

Power supply value	12 to 30 VDC
Current consumption	120 mA 85 mA

Physical

Net weight	380 g
Colour	Sort
Material	Polycarbonat

Environmental

Operating temperature	-25 to +60°C
Environment	Udendørs

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57