FD310

End-to-end Beam Detector - 5 to 120 m



Details

- Separate Transmitter and Receiver Heads
- Range 5 to 120 metres, configurable per set of Detectors
- Integral Laser Alignment in Receiver
- 2-wire Interface between Controller and Receiver
- Single and Twin Detector options
- Separate Fire and Fault Relays per Detector
- Low Level Controller with LCD display
- Programmable Sensitivity and Fire Threshold
- Automatic Gain Control (AGC) for drift compensation
- First Fix concept for Transmitter, Receiver and Controller
- Multiple cable gland knockouts for ease of wiring
- Optional Transmitter powering from Controller

FD310

End-to-end Beam Detector - 5 to 120 m

Technische specificaties

Physical

Colour	Hvid
Mounting type	Vægmontering

Environmental

Environment	Indendør

Regulatory

Certification	EN54-12

Compatibele producten

Categorie	Referentie	Beschrijving
Detection device	FD310H	Additional Detector Pair, 5 - 120M, For Use With FD310

EDWARDS
Built for Resilience

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57