SH-62-0210-0001-99

SmartCell Wireless Remote Indicator

Overview

The SmartCell wireless remote indicator is quick and easy to install and offers individual addressing at the Excellence control panel or Gateway.

Features include red fire indication LED, bidirectional 868 MHz communication and an anti-tamper locking mechanism.

This device is third party certified and compatible with the Excellence wireless gateway.



Details

- Fully wireless
- Quick and easy to install
- Red fire indication LED
- Unique design
- Inbuilt locking mechanism

SH-62-0210-0001-99
SmartCell Wireless Remote Indicator

Technical specifications

General

Wireless frequency	868 MHz
Compatibility	Excellence Gateway

Electrical

Power supply type	Batterie
Batteries	3 x 3.6 V lithium thionyl chloride batteries. Fanso: ER14505M HCB: ER14505M (HCB-JS-TZ-02-547)
Power consumption	1.46 W max.
Operating voltage	2.7 to 3.65 VDC
Current consumption	0.1 to 400 mA

Physical

Physical dimensions	110 x 39 mm (Ø x D)
Colour	Hvid
Mounting type	Vægmontering
Mounting base	Senza fili

Environmental

Vandal proof	Yes
Operating temperature	-10 to +55 °C
Storage temperature	-10 to +30 °C (with batteries)
Relative humidity	0 to 95% noncondensing
Environment	Indendør
IP rating	IP21C

Regulatory

Compliancy	CE, REACH, RED (2014/53/EU), RoHS 3, WEEE
Certification	CPR
Standards	EN54-13 EN54-25

Compatible products

Category	Reference	Description
Batteries	SH-836-000	AA ER14505M 3.6V Lithium Battery
Interface unit	SH-14-3201-000 1-99	Excellence SmartCell Addressable Wireless Gateway
Test Equipment	SH-21-BASE-020 0	SmartCell Device / Sounder base – White (10 pack)

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 22 May 2026 - 10:45