IM1640PAG-G3

Surface Mount Contact, Armored Cable, EN Grade 3 & NFA2P 3 shields

Commercial Surface Mount Contact

The IM1640 series commercial surface mount contacts are specifically designed to work on metal frames. The contacts can be used in harsh environments. Special version with armoured cable and including junction box is available.



Details

- Designed for use in harsh environments
- Tamper loop
- Version with armored cable

IM1640PAG-G3

Surface Mount Contact, Armored Cable, EN Grade 3 & NFA2P 3 shields

Technical specifications

General

Application type	Montaggio a superficie
Contact type	NC
Connectivity	4 wires, 2 meters (armored cable)

Wired/wireless

Wired-wireless	Kablede
Operating gap	15 mm

Electrical

Cable length	2 m
Voltage	max. 40 VDC
Switching current	max. 500 mA

Physical

Physical dimensions	58 x 22 x 12 mm (W x H x D)
Dimensions magnet	8 x 30 mm
Dimensions contact / sensor	8 x 30 mm
Colour	Hvid
Material	ABS

Environmental

Operating temperature	-40° to +70° C
IP rating	IP67

Regulatory

EN50131 grade	Lønklasse 3
Compliancy	CE
Certification	NFA2P

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 5 June 2026 - 12:25