AB305N

LED beacon, white base, white lens

General

The AB305N is a general purpose red LED beacon which can be used in various applications. Utilising modern LED components to provide a high level of visual indication and offering longer expected component life.

Greater visibility

The AB305N beacon is fitted with a diffuser for greater visibility and spread of light.

Locking mechanism

The mechanism for locking the beacon to the base is activated by default, but can be disabled if required. A special tool is required to remove the beacon from the base, if the locking mechanism is active.



Details

- Interfere-less safety locking head to base
- Weather proof / IP65
- 12V to 30 VDC
- Long life LED design
- White high quality polycarbonate housing
- Removable connection terminal

AB305N

LED beacon, white base, white lens

Technical specifications

General

Accessory group	Beacon
Type	Tilbehør

Flash specifications

Flash frequency	1 Hz

Electrical

Operating voltage	10 to 30 VDC
Current consumption	30 mA

Physical

Physical dimensions	85 x 81 mm (Ø x D)
Shipping weight	144 g
Material	Policarbonato alto impatto

Environmental

Operating temperature	-20 to 60°C
IP rating	IP65

Regulatory

Compliancy	CE

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 9 January 2026 - 9:45