TVM-2414

Moniteur LED TruVision 24", VGA, HDMI, haut-parleur audio, entrée audio stéréo, Full HD, 1920 x 1080

Overview

The LED TVM range of monitors is the latest advancement in TruVision monitors. Providing superior image quality through HDMI or VGA connections, these monitors are a great fit for today's demanding video surveillance market.
Whether displaying analog or IP resolutions, these monitors are designed to provide top image quality paired with industrial reliability.

These monitors are designed to perform 24/7 and are design with security applications in mind.



Capabilities

The TVM-2414 is a 24" class monitor, offering HDMI and VGA connections. The monitor is provided with VESA wall mount holes, making them easy to combine with a variety of TruVision mounting accessories. The on screen display allows for full control of images settings such as brightness, contrast and colour temperature.

Détails

- Rétro-éclairage LED de 24 pouces
- Résolution Full HD
- Cadre ultra-mince avec bordure ultra-fine sur les 3 côtés
- Format 16:9
- Résolution recommandée : 1920 x 1080
- Rapport de contraste de 4000:1 pour des images nettes
- Entrées multiples, y compris VGA, HDMI

TVM-2414

Moniteur LED TruVision 24", VGA, HDMI, haut-parleur audio, entrée audio stéréo, Full HD, 1920 x 1080

Spécifications techniques

General

Technology	LED
VESA compatibility	100 x 100 mm
Included accessories	Manuale, Cavo di alimentazione
Bezel width	1.8 mm (top/left/right), 21.4 mm (bottom)

Display

Screen size	23.8”
Aspect ratio	16:9
Contrast ratio	4000:1
Pixel pitch	0.2745 (H) × 0.2745 (V) mm
Viewing angle (H/V)	178° / 178°
Response time	6.5 ms (typ) (G to G) OD 5 ms
Brightness	250 cd/m² (Typ)
Recommended resolution	1920 x 1080 @ 60 HZ
Backlight	E-LED
Color depth	8 bit
Active display area	527.04 (H) × 296.46 mm (V)
Haze	Anti-Glare, 3H (Without Haze)

Interface

BNC video I/O	No
VGA video in	Yes
HDMI video in	1
PC stereo in	Yes
Audio out	No

Operations

Controls	Power, Up/Down, Left/Right, Source, OSD Menu
OSD	English, French, Spanish, German, Italian, Portuguese, Netherlands, Russian, Turkish, Polish
Remote control support	No

Electrical

Power supply type	100 bis 240 VAC
Power consumption	<25 W
Standby power consumption	≤ 0.5 W
Power supply	DC 12 V, 2.5 A

Physical

Physical dimensions	538 × 326 × 37 (without stand) 538 × 407 × 186 (with stand)
Net weight	2.63 kg
Shipping weight	3.34 kg
Colour	Schwarz
Housing Type	Plastik

Environmental

Operating temperature	0 to 40°C
Storage temperature	-20 to 60°C
Relative humidity	20 to 90% noncondensing
Environment	Drinnen

Regulatory

Compliancy	CE, UKCA

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web fr.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 12 November 2026 - 20:20