PB611M

AIR detector



Details

- Range 100 metres
- Outdoor installation
- 4 Synchronised lines
- 4 Optional frequency steps ensure that one receiver will only 'see' one transmitter
- Adjustable precision optics
- Immune to external light
- High protection against EMC noise
- AGC sensitivity control
- Extra lens heater available as an accessory
- Full range of tower accessories for outdoor fitting
- Visibility control is standard
- Tone signal for correct adjustment
- Alarm memory

PB611M
AIR detector

Technische specificaties

General

Category	Aktive Infrarøde Stråler
Product type	Aktiv Infrarød Stråle
Infrared system	4-beam LED, double frequency modulation
Tamper	NC (max. charge 30 VAC/VDC - 100 mA)

Detection

Range	100 m
Alarm response time	51 to 700 ms

Inputs/outputs

Alarm output	NC/NO (max. charge 30 VAC/VDC - 0.5 mA)
Supervision output	NC/NO (max. charge 30 VAC/VDC - 1 A)

Electrical

Power supply value	12 to 30 VDC
Current consumption	105 mA 70 mA

Physical

Net weight	1.2 g
Colour	Sort

Environmental

Operating temperature	-35 to +66°C
Environment	Udendørs

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57