IM1640PAG01JB

Surface Mount Contact, 1 M Armoured Cable, Junction Box, NFA2P

Commercial Surface Mount Contact

The IM1640 series commercial surface mount contacts are specifically designed to work on metal frames. The contacts can be used in harsh environments. Special version with armoured cable and including junction box is available.



Details

- Designed for use in harsh environments
- Magnet specifically designed to work on metal frames
- Tamper loop
- Version with armoured cable

IM1640PAG01JB

Surface Mount Contact, 1 M Armoured Cable, Junction Box, NFA2P

Technical specifications

General

Application type	Montaggio a superficie
Contact type	NC
Connectivity	4 wires, 100 cm (armoured cable)

Wired/wireless

Wired-wireless	Kablede
Operating gap	25 mm, 35 mm max.

Electrical

Voltage	max. 48 VDC

Physical

Physical dimensions	72 x 23 x 19 mm (W x H x D)
Dimensions magnet	23 x 72 mm
Dimensions contact / sensor	23 x 72 mm
Colour	Hvid

Environmental

Operating temperature	-10° to +55° C

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 13 August 2026 - 11:05