SC-21-0200-0001-99

SmartCell Dual Smoke/Heat Detector

Overview

The SmartCell Dual Smoke / Heat Detector is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include dual smoke and/or heat detection, bidirectional 868 MHz communication, fire indication LED and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



Details

- Fully wireless
- Quick and easy to install
- Compact profile
- Flexible detection; smoke and/or heat
- Unique design
- Inbuilt locking mechanism

SC-21-0200-0001-99
SmartCell Dual Smoke/Heat Detector

Technical specifications

General

Wireless frequency	868 MHz
Compatibility	SmartCell, Excellence Gateway

Electrical

Batteries	3 x 3.6 V lithium thionyl chloride batteries. Fanso: ER14505M HCB: ER14505M (HCB-JS-TZ-02-547)

Detection

Sensitivity	Smoke: Normal, Normal+AVF. Heat: 58 °C, static (A2S), 58 °C rate of rise (A2R), 72 °C static (BS), 72 °C rate of rise (BR)

Physical

Physical dimensions	110 x 58 mm (Ø x D)
Net weight	0.2 kg
Colour	Hvid
Mounting type	Loftmontering

Environmental

Operating temperature	-10 to +55°C
Storage temperature	-10 to +30°C (with batteries) -10 to +55°C (without batteries)
Relative humidity	95% noncondensing max.
Environment	Indendør

Regulatory

Compliancy	CE
Certification	CPR
Standards	EN54-5 EN54-7 EN54-13 EN54-25

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 26 May 2026 - 15:37