FE245

Retenedor electromagnético de 400N para montaje en pared con pulsador de desbloqueo.

General

The FE245 is a wall mount door holder, in a Bayblend housing, which offers a 400N holding force and a release button.

Magnet construction

The magnet is constructed with a pressed coil and anti-remenance pin, giving it a protection of IP54. The protection diodes are integrated into this construction.

Housing

The plastic housing is manufactured from Bayblend and contains 30% PA6 glass fiber, which makes it much stronger than standard ABS. Bayblend offers high heat resistance, high impact and notched impact strength, and high stiffness and dimensional stability.

Installer friendly

- For practical ease of installation, the door holder comes complete with electrical screw terminals.
- The housing is predrilled in a practical, standard format for rapid mounting.
- The door holder is supplied complete with a keeper plate, which offer angular adjustment.

Approvals

The FE245 is fully approved according to EN1155.



Detalles

- Low power - 1.6 W
- 400 N holding force
- Anti-remnant ejector
- Spark suppression diode and reverse polarity protection
- Release button
- EN1155 approved
- Keeper plate included

FE245

Retenedor electromagnético de 400N para montaje en pared con pulsador de desbloqueo.

Especificaciones técnicas

General

Release button	Yes

Electrical

Power supply type	24 VDC

Productos compatibles

Categoría	Referencia	Descripción
Door Holders	FE527	Base cuadrada estándar de acero. Dimensiones: 55x18mm.
Door Holders	FE529	Base cuadrada estándar de acero. Eslabón giratorio de 120 grados. Dimensiones: 55x50mm.

Como empresa innovadora, Kidde Global Solutions se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 12 November 2026 - 18:57