# VVS300-PLUS

**Seismic detector for safes and vaults, NC contact**



# VVS300-PLUS

## Seismic detector for safes and vaults, NC contact

## Technische specificaties

### General

| | |
|---|---|
| Application type | Safe, Vault |
| Tamper protection | Temperature 84°C, drill shield, opening contact, pry-off contact |
| Alarm indication | LED-indication screw no. 3 |
| Low voltage alarm | 7.5 V |

### Detection

| | |
|---|---|
| Range | 3 to 14 m radius |
| Sensitivity adjustment | 5 steps of approx. 6 dB each |

### Inputs/outputs

| | |
|---|---|
| Alarm contact | NC |
| Test output | Yes |

### Electrical

| | |
|---|---|
| Power supply value | 9 to 15 VDC |
| Current consumption | 8.6 mA |

### Physical

| | |
|---|---|
| Physical dimensions | 81 × 101 × 28 mm |
| Net weight | 380 g |
| Colour | Grey (RAL 7035) |

### Environmental

| | |
|---|---|
| Operating temperature | -20 to +55°C |
| Relative humidity | 90% |
| IP rating | IP30 |

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57