# ACT430E-5

**(5-pack) Mifare Classic S50 with 7-byte UID (CSN) Keyfob. For use on with ATS1160N/1161N & ACI406/407 Mifare readers.**

## Product overview

These Mifare Classic 1k keyfobs are to be used on ATS1160N/ATS1161N, ACI406/ACI407 and any other KGS Fire & Security Mifare or Transition reader supporting 7-byte Card Serial Numbers (CSN). The cards are unprogrammed and only the unique 7-byte ID-number of the Mifare® chip, the so called Chip or Card Identification Number (CSN) is used by the readers.



## Details

- Read only for CSN (7-byte)
- Read / Write function for card sectors

# ACT430E-5

## (5-pack) Mifare Classic S50 with 7-byte UID (CSN) Keyfob. For use on with ATS1160N/1161N & ACI406/407 Mifare readers.

## Technical specifications

### System

| | |
|---|---|
| Reading distance | 0 to 10 cm |
| Memory size | 1 kB |
| No. of Mifare bytes CSN | 7 bajtów (S50) |
| Supported readers | Czytniki ACI406/407 Mifare, Czytniki ATS1160/1161 Mifare |

### Technology

| | |
|---|---|
| Credential type | Nærhed |
| Credential operating frequency | 13.56 MHz |
| Supported technology 13.56 MHz | MIFARE Classic (CSN) |

### Ordering information

| | |
|---|---|
| Cards/tags in package | 1 |

### Physical

| | |
|---|---|
| Material | PA6 |
| Form factor | Brelok |
| Physical dimensions | 45 x 30 x 14 mm |
| Net weight | 16 g |
| Colour | Sort |

### Environmental

| | |
|---|---|
| IP rating | IP66 |

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 18 June 2026 - 14:24