40-K-10

Signo 40/40K Reader, 1 Inch Spacer, Black

HID® Signo™ Readers

HID® Signo™ is the signature line of physical access control readers from HID Global. The versatility, performance and connected capabilities of HID Signo readers offers a highly adaptable, interoperable and secure approach to electronic access control. HID Signo affords security system installers and administrators a simple and effective approach to secure access control for almost any scenario.

With support for a wide array of credential technologies — past, present and future — HID Signo is a good choice for those looking to make the transition to another technology. HID Signo readers are designed to be connected and managed via HID Reader Manager® remotely by Bluetooth. For some settings the reader will need to be re-powered. This allows for access control systems to dynamically respond as new needs, configurations or threats arise.

The signature line of readers from HID Global

Highly Versatile - Support for a wide range of credential technologies, including HID Mobile Access® via native Bluetooth and Near Field Communication (NFC).

Optimized Performance - Ultra secure storage of cryptographic keys on certified secure element hardware, plus a new surface detection feature that enables the reader to automatically recalibrate and optimize read range performance.

Connected to the Future - All readers include out-of-the-box support for Open Supervised Device Protocol (OSDP) for secure bidirectional communication.

Hands free management - No need to interact with the device. Go mobile with native Bluetooth and NFC support.

Migration - Integrated 125 kHz credential read support for easy migration. Supports a variety of common credential technologies. Deactivate legacy credential technology will conclude secure migration.

Mounting - Flush mount terminal block and pigtail wiring options. Robust outdoor performance with an IP65 rating.

Configuration - No configuration cards are available, configuration settings are managed via a mobile device using Reader Manager.



Details

- Multi-Layered security to ensure data authenticity and privacy
- EAL 6+ Certified Secure Element Hardware
- Native OSDP secure channel capability
- Trusted secure authentication using the SIO data model
- Supports iCLASS Elite™ and Corporate 1000 Programs
- Go mobile with native Bluetooth and NFC support
- Integrated 125 kHz credential read support for easy migration
- Supports over 15 common credential technologies
- Flush mount terminal block and pigtail wiring options
- Robust outdoor performance with an IP65 rating
- Easily and securely managed using HID Reader Manager®
- Configure via a mobile device or OSDP
- Update firmware in response to threats
- Personalize by configuring audio visual or keypad settings
- Deactivate legacy credential technology to conclude secure migration
- Mobile-ready by default, including Apple's Enhanced Contactless Polling (ECP) to support credentials in Apple Wallet
- Designed to seamlessly integrate into the HID Origo® ecosystem

40-K-10

Signo 40/40K Reader, 1 Inch Spacer, Black

Technical specifications

System

Reader accessory	1 inch spacer
Language installation manual	English

Technology

Reader type	Spacer

Tamper type

Pry-off tamper	No
Opening tamper	Yes

Operation

PIN keypad	No

Support

Language installation manual	English

Physical

Physical dimensions	80 x 121.5 x 25.4 mm
Colour	Sort
Material	Poliwęglan - UL94V-0
Form factor	Mullion
Mounting type	Montaż nawierzchniowy, Vægmontering

Environmental

Vandal proof	No
Environment	Indendør, Udendørs
Operating temperature	-35 to +66°C
Relative humidity	0 to 95% noncondensing

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 21 May 2024 - 14:06