AS620RF-N

Sirène extérieure sans fil autonome comprenant un transcepteur et un bloc-batterie, 868 MHz.

The AS620RF-N self-powered siren is a stand-alone two-way wireless siren for outdoor applications. It is compatible with the transceiver module AS620RF-TR-N which is included.

The siren is protected against the removal of its cover and against being removed from the wall. It has an internal polycarbonate cover. It can receive signals from the AS620RF-TR-N transceiver for alarm activation and system status. The siren will send a signal back to the transceiver in case it detects a tamper condition, supervision fault, low battery or a system fault.

Optionally, up to 4 remote controls can be added to allow the end-user to operate additional outputs through his security system in a quick and easy way.



Détails

- Solution « design » sans fil complète comprenant une sirène extérieure et une télécommande (en option)
- Solution sans fil autonome bidirectionnelle
- Batterie incluse
- Double protection contre les tentatives de sabotage : anti-ouverture et anti-démontage du mur
- Système mécanique anti-mousse
- Système anti-perforation
- Diverses options de programmation et de minuterie
- Supervision, autoprotection, batterie faible et indication de défaut
- lumière stroboscopique LED multicolore

AS620RF-N

Sirène extérieure sans fil autonome comprenant un transcepteur et un bloc-batterie, 868 MHz.

Spécifications techniques

General

Sounder output (dB @ distance)	105 dB at 1 m (typical)
Operating frequency	868 MHz
Cut-off timer	30 s, 60 s, 120 s, 300 s
Maximum transmission power	2 mW
Wireless signal range	500 m in open field

Electrical

Operating voltage	7.5 Vdc battery pack
Current consumption	160 µA (standby) 250 mA (alarm)

Physical

Physical dimensions	312 x 236 x 109 mm
Shipping weight	2866 g (w/o battery)

Environmental

Operating temperature	-10 to +50°C
IP rating	IP44

Regulatory

Compliancy	RED (2014/53/EU)

Produits compatibles

Catégorie	Référence	Description
Accessories	AS620RF-BP	Batterie de rechange pour AS620RF(-N), 7,5 VDC (5 x 1,5 piles alcalines de taille « D »).
Accessories	AS620RF-TR-N	Module transcepteur 868 Mhz pour AS620RF-N.

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web fr.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 12 November 2026 - 18:57