# DC106R4.7


## Recessed mount contact, flanged

### Recessed contacts

The DC106 recessed contacts are designed for applications where the added integrity of mouting screws is needed. The units can be used in wooden and metal frame doors and windows.

### Easy installation

The two mounting holes provide additional strength to prevent the contact and magnet from becoming dislodged due to environmental changes. This can occur when the door or window frames become warped and misaligned from moisture or the settling of a building.



### Details

- Flange mounting for positive mounting
- Attractive, added security of recessed installation
- Easy installation
- Standard 2.5 m wire length
- Tamper loop provided
- Built-in resistors available to special order
- Mounting screws supplied

# DC106R4.7

## Recessed mount contact, flanged

## Technical specifications

### General

| | |
|---|---|
| Application type | Montagem Embutida |
| Contact type | Resistencia de 4K7 |
| Connectivity | 4 wires, 2.5 m |

### Wired/wireless

| | |
|---|---|
| Wired-wireless | Kablede |
| Operating gap | 23 mm |

### Physical


| | |
|---|---|
| Physical dimensions | 19 x 33 mm |
| Dimensions magnet | 19 x 33 mm |
| Diameter | 9.5 mm |
| Borehole diameter | 9.5 mm |
| Colour | Hvid |

### Environmental

| | |
|---|---|
| Operating temperature | -40 to +65°C |

### Regulatory

| | |
|---|---|
| EN50131 grade | Lønklasse 2 |



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 13 August 2026 - 11:05