ATS1140

Écran tactile 7" pour centrales Everon (ATSx700) et Advisor Advanced avec lecteur Mifare Secure intégré.

At a glance

The Advisor Advanced product family has a new addition: the ATS1140 graphical touchscreen. This device offers simple fingertip control of the security system with a 7-inch high-responsive touchscreen display that features easy-to-understand graphics. The ATS1140 is designed to perfectly complement other control units in the Advisor Advance security system family, ensuring a smooth user experience.

The ATS1140 boasts a modern design with a new graphical user interface that features icon-based and readable text. The display's contrast and the built-in buzzer's volume level can be adjusted via the configuration board. This device also comes with a simplified and intuitive graphical user interface, allowing users to easily navigate the programming, operational features, dashboard, system status, alarms, logs, and additional function keys.

Overall, the ATS1140 graphical touchscreen combines functionality and style to provide an efficient and user-friendly experience.



Built-in secure card reader

The ATS1140 is equipped with a Mifare Desfire EV1/EV2/EV3 card reader that is built-in. When the device is in secure mode, the data is encrypted from the card to the keypad and from the keypad to the Advisor Advanced control panel.

The ATS1140 can be used for arming/disarming the system with the PIN code, the card or a combination of both for enhanced security. It works with the multiple card badging solutions that are available in the Advisor Advanced product family.
Alarm system activation: a user can turn on the alarm system by badging their card three times within a 10-second interval.
Door access control: doors can be programmed for specific behaviors based on badging with the card. For example, with a single badge scan, granting seamless entry and exit without requiring a card, and a triple badge scan will promptly re-lock the door, providing enhanced convenience for the end user.

Quick access

The touch display menus are thoughtfully organized, featuring a clean and intuitive design that makes navigation a breeze. The single-touch operation eliminates the need for complex maneuvers, allowing for effortless interaction with the system. Whether you are an advanced tech user or a novice, you will find the touch display menus to be user-friendly and highly accessible.

Quick and easy installation

Screw the back plate onto the wall, connect the data bus cable from the panel, snap the touchscreen onto the plate: you're all set up and ready to go.

Détails

- Conception moderne et épurée
- Interface graphique simplifiée et intuitive
- Écran tactile couleur de 7 pouces
- Possibilité d'ajouter un logo personnalisé sur l'affichage
- Touches de fonction programmables et rapidement accessibles
- Lecteur sécurisé Mifare Desfire EV1/EV2/EV3 intégré
- LCD, buzzer et éclairage des touches réglables par l'utilisateur
- Utiliser des cartes sécurisées de la série ATS145x ou des cartes personnalisées (sauf ATS1458)
- Interface utilisateur intuitive et simplifiée, basée sur des icônes
- Prise en charge multilingue
- Clavier virtuel
- NFA2P

This installation method is not only easy to follow, but it also ensures a secure fit for your touchscreen, providing you with peace of mind knowing that your device won't fall off the wall.
In order to connect the Advisor Advance security system to ATS1140, the panel must have MR4.10 or later. Please contact your local support for assistance if needed.

ATS1140

Écran tactile 7" pour centrales Everon (ATSx700) et Advisor Advanced avec lecteur Mifare Secure intégré.

Spécifications techniques

General

User interface	Teclas Superficiais de Resposta ao Toque
Product line	Advisor Advanced, Everon
Status LEDs	1
Integrated reader	Segura MIFARE
Language	Multi-language support
Supported Firmware	MR4.10 or later

System

Function keys	3
Supported card types	MIFARE® Classic UID, MIFARE® DESFire® EV1, MIFARE® DESFire® EV2, MIFARE® DESFire® EV3
Addressing type	Endereçamento Software
Supported cable type	WCAT 52/54 or equivalent

Communication

Communication type	Verdrahtet
Reading distance	Up to 3 cm
Wiring	RS-485, 4-wire bus

Inputs/Outputs

Inputs	1
Input type	Request to Exit (NO)
Outputs	1
Output type	Open collector (OC), 100 mA max, 15 VDC max.

Electrical

Operating voltage	12.0 to 13.5 VDC (provided by panel)
Current consumption	330 mA at 13.7 VDC, 375mA at 12 VDC (max) 220 mA at 13.7 VDC, 250mA at 12 VDC (average) 70 mA at 13.7 VDC, 80 mA at 12 VDC (standby)

Physical

Physical dimensions	127 x 179 x 20 mm
Net weight	460 g
Colour	Weiß
Mounting type	Wandmontage
Material	ABS Plastik

Environmental

Operating temperature	0 to +50°C
Relative humidity	up to 95% non-condensing
Environment	Drinnen

Regulatory

Certification	EN50131 Grau 3, F&P, FG, IMQ, INCERT, NFA2P, SBSC

Produits compatibles

Catégorie	Référence	Description
Control Panel	ATS1700-MM	Always On. Always Aware. Centrale d'alarme Everon, carte IP, EN grade 3, NFA2P GR2+RTC, WebApp, 8 à 48 zones, 4 groupes, boîtier métallique de taille moyenne, multilingue.
Control Panel	ATS3700-MM	Always On. Always Aware. Centrale d'alarme Everon 3700, IP embarqué, EN grade 3, NFA2P Gr3+RTC WebApp, 16 entrées embarquées max 256 zones, 16 groupes, boîtier métallique moyen, multilingue.
Control Panel	ATS4700-LM	Always On. Always Aware. Centrale Everon 4700, carte IP, EN grade 3, NFA2P Grade 3 + RTC, WebApp, 16 zones embarquées max 1000 zones, 64 groupes, boîtier métallique de grande taille.
Control Panel	ATS4700-MM	Always On. Always Aware. Centrale d'alarme Everon 4700, carte IP, EN grade 3, WebApp, 16 à 1000 zones, 64 secteurs, boîtier métallique de taille moyenne, multilingue.

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web fr.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 12 November 2026 - 18:57