# AS600FLASH

**Flash module for AS 600 Series**



## Details

- Attractively shaped housings
- High-quality dual skinned design
- 120 dB @ 1 m sound output
- 300 x 210 x 87 mm
- Lead acid battery back-up for up to 7.2 Ah
- Steel inner cover with foam resistant grid
- Fully potted electronics
- Pry-off and opening tamper detection
- Strobe flash light
- Self detection of cable cutting or tampering
- Installer friendly
- Automatic polarity selection
- Independent hold-off for both beacon and siren
- Choice of cut-off time

# AS600FLASH

## Flash module for AS 600 Series

## Technical specifications

### General

| | |
|---|---|
| Accessory group | Sirene |
| Type | Reservedel |

### Flash specifications

| | |
|---|---|
| Current consumption | 110 mA |
| Light output | 100,000 peak lumens |
| Flash frequency | 60 flashes/minute |

### Electrical

| | |
|---|---|
| Power supply value | 10.5 to 13.8 VDC |
| Operating voltage | 13 to 14.2 V |
| Current consumption | 700 mA |

### Physical

| | |
|---|---|
| Physical dimensions | 300 x 210 x 87 mm |
| Net weight | 3 kg |
| Material | Polykarbonat / Inox |

### Environmental

| | |
|---|---|
| Operating temperature | -25 to 55°C |

### Sounder

| | |
|---|---|
| Sound output at 1 m | 110 dB |
| Frequency | 0.7 to 1.2 kHz |

### Beacon

| | |
|---|---|
| Spike suppression network | Standard fitted |

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 21 January 2026 - 19:51